

# Eaton MBS33NSB40BW

Catalog Number: MBS33NSB40BW

MBS, 3Ph/3Ph, 8-20kVA, 16mm<sup>2</sup>, Bottom Entry, w/o separate bypass input



## General specifications

Product Name	Catalog Number
Eaton Hotswap MBP Maintenance Bypass Enclosure Wraparound Single Input	MBS33NSB40BW
Product Height	Product Length/Depth
492 mm	272 mm
Product Weight	Product Width
15 kg	368 mm
	Certifications
	Contact Manufacturer

**Construction type**

Free standing model

**Color**

Black

**Auto shutdown function**

No

**Type of Accessory**

Bypass

**Used with**

93PS, 93E, 93PR, 93PM

**Input connection**

Hardwired/fixed connection

**Input nominal voltage**

230V default (220/230/240V)

**Nominal frequency**

50-60 Hz

**Input frequency range**

50Hz-60Hz

**Number of outputs hardwired**

1

**Output nominal voltage**

230V default (220/230/240V)

**Electric current - max**

40A

**Feed type**

1

**Transfer time**

0 ms

**Standard factory warranty**

1 Year

**Communication**

Voltage-free relay interlock

**Potential free switch contact**

Yes

**Altitude**

0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)

Input voltage range

192-264 V

Output frequency

50-60 Hz

Output voltage range

192-264 V

Phase (input)

Three-phase

Phase (output)

Three-phase



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)