



Performance & Technical Specifications

PERFORMANCE	Model Number	CSUV-UG6CX
	Sanitation Cycle	20 Seconds
	Power ON	24/7
PHYSICAL DIMENSION	Lid Closed	L 26.7" x W 16.5" x H 12.3" (L 68cm x W 42cm x H 31.3cm)
	Lid Open	L 26.7" x W 16.5" x H 21.2" (L 68cm x W 42cm x H 53.9cm)
	Weight / Desktop Footprint	37lb (17kg) / 15.7" x 16.45" (40 x 42cm)
	Tray Dimensions	L 9.4" x W 12.87" x H 3.45" (L 24cm x W 32.7cm x H 8.8cm)
ENVIRONMENTAL	Operating Temperature	5° C / 41° F to 40° C / 104° F
	Humidity	50% @ 40° C / 104° F - 81% @ 31° C / 88° F
	Noise	< 35dB
	Pressure	Atmospheric (101.3 kPa)
ELECTRICAL	Voltage	120 / 240VAC, 50/60Hz
	Power Consumption - Idle	100W (idle), 130W (cycle)
	Fuse	5 x 20mm 3A 250V
BULBS	Germicidal UV-C bulbs	Six (three upper and three lower)
	UV Dosage	240 mJ/cm ² (20 second cycle)
USER INTERFACE	Lid Open	Automatic
	Lid Contact Surface	Antimicrobial silver sheet
	Touch Screen	Yes
	Cycle Abort (Stop Button)	Yes
MISCELLANEOUS	Initial Warm-up time	60 Seconds
REGULATORY	Electrical Safety	IEC 61010-1
	Emission (EMI/EMC)	Class A limits of IEC 61326, FCC Part 15 Subpart B and ICES-003
	Wireless Transmitter	FCC and CE certified
	CE Marking	Yes
	RoHS Compliant	Yes



CANADA

70 Richmond St E., Suite 201
Toronto, ON Canada
M5C 1N8

USA

1170 Main St
Buffalo, NY USA
14209

cleanslateuv.com

sales@cleanslateuv.com
+ 1 877 553 6778