



PM-5K

PANEL MOUNT KEYBOARD WITH HULAPOINT II?

The PM-5K combines a HulaPoint II? pointing device and a 10-key numeric keypad in a ruggedized stainless steel case to provide dual functionality. This keyboard also offers user Windows keys for ease of access to the operating system. Its integrated HulaPoint II? pointing device makes the PM-5K a total solution in one convenient package.

Features:

- 10-Key Numeric Pad
- 20 Function Keys
- Integrated HulaPoint II? Pointing Device
- USB, PS/2 and AT/serial configurations available

Product Code PM-5K

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/serial Cable (providing separate keyboard and mouse connections), or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2 or AT/Serial: KEYBOARD: 50mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB: 85mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
WEIGHT	5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	17.70" x 9.20" x 1.58" (w-h-d) 449.6mm x 233.7mm x 40.1mm
MODEL NUMBERS	PM-5K-PS2: With PS/2 cable PM-5K-USB: With USB cable PM-5K-STD: With AT/serial cable