

SLK-101-M

Backlit Mobile Industrial Keyboard

iKey®'s SlimKey® SLK-101-M keyboard provides full-size versatility in a rugged, compact design. It features red LED backlit keys for use in areas with minimal lighting. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the SlimKey® SLK-101-M is ideal for use in industrial, medical and material handling applications. Its large numeric pads allow for easy data entry, while its robust polycarbonate cases have built-in mounting holes for convenient vehicle use. Ask us about using this keyboard with Zebra and Honeywell product scanner devices.

Features:

- 10-Key Numeric Pad
- 12 Function Keys
- Built-In Mounting Holes
- Integrated Backlighting
- MS Windows™ Function Keys
- USB and PS/2 configurations available



Product Code SLK-101-M

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B, IP 65
SHOCK	3x11 ms pulses of 50g on each of 3 axis
CABLE	LENGTH: 10' straight (3 m)
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 210mA@5V (from Keyboard port) USB: 210mA@5V (from CPU port)
FLAMMABILITY	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	2 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant

DIMENSIONS

14.74" x 5.69" x 1.61" (w-h-d) 374.4mm x 144.5mm x 40.9mm
